

# 1 Introduction

This document lists C++ coding recommendations common in the C++ development community.

The recommendations are based on established standards collected from a number of sources, individual experience, local requirements/needs, as well as suggestions given in [\[1\]](#) - [\[4\]](#).

There are several reasons for introducing a new guideline rather than just referring to the ones above. Main reason is that these guides are far too general in their scope and that more specific rules (especially naming rules) need to be established.

While a given development environment (IDE) can improve the readability of code by access visibility, color coding, automatic formatting and so on, the programmer should never rely on such features. Source code should always be considered larger than the IDE it is developed within and should be written in a way that maximize its readability independent of any IDE.

## 1.1 Layout of the Recommendations.

The recommendations are grouped by topic and each recommendation is numbered to make it easier to refer to during reviews.

Layout of the recommendations is as follows:

Guideline short description
Example if applicable
Motivation, background and additional information.

The motivation section is important. Coding standards and guidelines tend to start "religious wars", and it is important to state the background for the recommendation.

## 1.2 Recommendation Importance

In the guideline sections the terms must, should and can have special meaning. A must requirement must be followed, a should is a strong recommendation, and a can is a general guideline.

## 2 General Recommendations

1. Any violation to the guide is allowed if it enhances readability.
The main goal of the recommendation is to improve readability and thereby the understanding and the maintainability and general quality of the code. It is impossible to cover all the specific cases in a general guide and the programmer should be flexible.

2. The rules can be violated if there are strong personal objections against them.
The attempt is to make a guideline, not to force a particular coding style onto individuals. Experienced programmers normally want adopt a style like this anyway, but having one, and at least requiring everyone to get familiar with it, usually makes people start thinking about programming style and evaluate their own habits in this area.
On the other hand, new and inexperienced programmers normally use a style guide as a convenience of getting into the programming jargon more easily.

## 3 Naming Conventions

### 3.1 General Naming Conventions

3. Names representing types must be in mixed case starting with upper case.

Line, SavingsAccount

Common practice in the C++ development community.

4. Variable names must be in mixed case starting with lower case.

line, savingsAccount

Common practice in the C++ development community. Makes variables easy to distinguish from types, and effectively resolves potential naming collision as in the declaration `Line line`;

5. Named constants (including enumeration values) must be all uppercase using underscore to separate words.

MAX\_ITERATIONS, COLOR\_RED, PI

Common practice in the C++ development community. In general, the use of such constants should be minimized. In many cases implementing the value as a method is a better choice:

```
int getMaxIterations() // NOT: MAX_ITERATIONS = 25
{
    return 25;
}
```

This form is both easier to read, and it ensures a unified interface towards class values.

6. Names representing methods or functions must be verbs and written in mixed case starting with lower case.

```
getName(), computeTotalWidth()
```

Common practice in the C++ development community. This is identical to variable names, but functions in C++ are already distinguishable from variables by their specific form.

7. Names representing namespaces should be all lowercase.

```
model::analyzer, io::iomanager, common::math::geometry
```

Common practice in the C++ development community.

8. Names representing template types should be a single uppercase letter.

```
template<class T> ... template<class C, class D> ...
```

Common practice in the C++ development community. This makes template names stand out relative to all other names used.

9. Abbreviations and acronyms must not be uppercase when used as name [4].

```
exportHtmlSource(); // NOT: exportHTMLSource();  
openDvdPlayer(); // NOT: openDVDPlayer();
```

Using all uppercase for the base name will give conflicts with the naming conventions given above. A variable of this type would have to be named dVD, hTML etc. which obviously is not very readable. Another problem is illustrated in the examples above; When the name is connected to another, the readability is seriously reduced; the word following the abbreviation does not stand out as it should.

10. Global variables should always be referred to using the :: operator.

```
::mainWindow.open(), ::applicationContext.getName()
```

In general, the use of global variables should be avoided. Consider using singleton objects instead.

11. Private class variables should have underscore suffix.

```
class SomeClass { private: int length_; }
```

Apart from its name and its type, the scope of a variable is its most important feature. Indicating class scope by using underscore makes it easy to distinguish class variables from local scratch variables. This is important because class variables are considered to have higher significance than method variables, and should be treated with special care by the programmer.

A side effect of the underscore naming convention is that it nicely resolves the problem of finding reasonable variable names for setter methods and constructors:

```
void setDepth (int depth)
{
    depth_ = depth;
}
```

An issue is whether the underscore should be added as a prefix or as a suffix. Both practices are commonly used, but the latter is recommended because it seems to best preserve the readability of the name.

It should be noted that scope identification in variables has been a controversial issue for quite some time. It seems, though, that this practice now is gaining acceptance and that it is becoming more and more common as a convention in the professional development community.

12. Generic variables should have the same name as their type.

```
void setTopic(Topic* topic) // NOT: void setTopic(Topic* value)
                           // NOT: void setTopic(Topic* aTopic)
                           // NOT: void setTopic(Topic* t)
void connect(Database* database) // NOT: void connect(Database* db)
                                // NOT: void connect (Database*
oracleDB)
```

Reduce complexity by reducing the number of terms and names used. Also makes it easy to deduce the type given a variable name only.

If for some reason this convention doesn't seem to fit it is a strong indication that the type name is badly chosen.

Non-generic variables have a role. These variables can often be named by combining role and type:

```
Point  startingPoint, centerPoint;
Name   loginName;
```

13. All names should be written in english.

```
fileName; // NOT: nomFichier
```

English is the preferred language for international development.

14. Variables with a large scope should have long names, variables with a small scope can have short names [1].

Scratch variables used for temporary storage or indices are best kept short. A programmer reading such variables should be able to assume that its value is not used outside a few lines of code. Common scratch variables for integers are i, j, k, m, n and for characters c and d.

15. The name of the object is implicit, and should be avoided in a method name.

```
line.getLength(); // NOT: line.getLineLength();
```

The latter seems natural in the class declaration, but proves superfluous in use, as shown in the example.

## 3.2 Specific Naming Conventions

17. The terms get/set must be used where an attribute is accessed directly.

```
employee.getName();  
employee.setName(name);  
matrix.getElement(2, 4);  
matrix.setElement(2, 4, value);
```

Common practice in the C++ development community. In Java this convention has become more or less standard.

18. The term compute can be used in methods where something is computed.

```
valueSet->computeAverage();  
matrix->computeInverse()
```

Give the reader the immediate clue that this is a potential time consuming operation, and if used repeatedly, he might consider caching the result. Consistent use of the term enhances readability.

19. The term find can be used in methods where something is looked up.

```
vertex.findNearestVertex();  
matrix.findMinElement();
```

Give the reader the immediate clue that this is a simple look up method with a minimum of computations involved. Consistent use of the term enhances readability.

20. The term initialize can be used where an object or a concept is established.

```
printer.initializeFontSet();
```

The american initialize should be preferred over the english initialise. Abbreviation init should be avoided.

21. Variables representing GUI components should be suffixed by the component type name.

mainWindow, propertiesDialog, widthScale, loginText, leftScrollbar, mainForm, fileMenu, minLabel, exitButton, yesToggle etc.

Enhances readability since the name gives the user an immediate clue of the type of the variable and thereby the objects resources.

22. Non-Plural form should be used on names representing a collection of objects.

```
Vector point;  
Int value[];
```

Might sound unnatural, but will fit better, particularly within loops :

```
for (int i = 0; i < 10; ++i) {  
    point[i]->getPosition(); // NOT points[i]  
}
```

23. The prefix n should be used for variables representing a number of objects.

nPoints, nLines

The notation is taken from mathematics where it is an established convention for indicating a number of objects.

24. The suffix No should be used for variables representing an entity number.

tableNo, employeeNo

The notation is taken from mathematics where it is an established convention for indicating an entity number.

An elegant alternative is to prefix such variables with an i: iTable, iEmployee. This effectively makes them named iterators.



25. Iterator variables should be called i, j, k etc.

```
for (int i = 0; i < nTables); i++) { : }
```

```
for (vector<MyClass>::iterator i = list.begin(); i != list.end();  
i++) {  
    Element element = *i;  
    ...  
}
```

The notation is taken from mathematics where it is an established convention for indicating iterators.

26. The prefix is should be used for boolean variables and methods.

isSet, isVisible, isFinished, isFound, isOpen

Common practice in the C++ development community and partially enforced in Java.

Using the is prefix solves a common problem of choosing bad boolean names like status or flag. isStatus or isFlag simply doesn't fit, and the programmer is forced to choose more meaningful names.

There are a few alternatives to the is prefix that fits better in some situations. These are the has, can and should prefixes:

```
bool hasLicense();  
bool canEvaluate();  
bool shouldSort();
```

27. Complement names must be used for complement operations [1].

get/set, add/remove, create/destroy, start/stop, insert/delete, increment/decrement, old/new, begin/end, first/last, up/down, min/max, next/previous, old/new, open/close, show/hide, suspend/resume, etc.

Reduce complexity by symmetry.

## 28. Abbreviations in names should be avoided.

```
computeAverage(); // NOT: compAvg();
```

There are two types of words to consider. First are the common words listed in a language dictionary. These must never be abbreviated. Never write:

cmd	instead of	command
cp	instead of	copy
pt	instead of	point
comp	instead of	compute
init	instead of	initialize

etc.

Then there are domain specific phrases that are more naturally known through their abbreviations/acronym. These phrases should be kept abbreviated. Never write:

HypertextMarkupLanguage	instead of	html
CentralProcessingUnit	instead of	cpu
PriceEarningRatio	instead of	pe

etc.

## 29. Naming pointers specifically should be avoided.

```
Line* line; // NOT: Line* pLine; // NOT: LIne* linePtr;
```

Many variables in a C/C++ environment are pointers, so a convention like this is almost impossible to follow. Also objects in C++ are often oblique types where the specific implementation should be ignored by the programmer. Only when the actual type of an object is of special significance, the name should emphasize the type.

## 30. Negated boolean variable names must be avoided.

```
bool isError; // NOT: isNoError bool isFound;
```

The problem arises when such a name is used in conjunction with the logical negation operator as this results in a double negative. It is not immediately apparent what `!isNotFound` means.

31. Enumeration constants can be prefixed by a common type name.

```
enum Color { COLOR_RED, COLOR_GREEN, COLOR_BLUE };
```

This gives additional information of where the declaration can be found, which constants belongs together, and what concept the constants represent.

An alternative approach is to always refer to the constants through their common type: `Color::RED`, `Airline::AIR_FRANCE` etc.

32. Exception classes should be suffixed with Exception.

```
class AccessException { : }
```

Exception classes are really not part of the main design of the program, and naming them like this makes them stand out relative to the other classes.

33. Functions (methods returning something) should be named after what they return and procedures (void methods) after what they do.

Increase readability. Makes it clear what the unit should do and especially all the things it is not supposed to do. This again makes it easier to keep the code clean of side effects.

## 4 Files

### 4.1 Source Files

34. C++ header files must have the extension `.h`. Source files can have the extension `.cpp` (recommended), `.c++` or `.cxx`. Template Implementation files can have the extension `.tpp` (recommended), or `.txx`.

```
MyClass.cpp, MyClass.h
```

These are all accepted C++ standards for file extension.

35. A class should be declared in a header file and defined in a source file where the name of the files match the name of the class.

MyClass.h, MyClass.cpp

Makes it easy to find the associated files of a given class. An obvious exception is template classes that must be both declared and defined inside a .h file, or declared in a header file and defined in a .cpp template implementation file.

36. All definitions should reside in source files.

```
class MyClass {  
public:  
    int getValue () {return value_;} // NO!  
    ...  
  
private:  
    int value_;  
}
```

The header files should declare an interface only, the source file (template implementation file, respectively) should implement it. When looking for an implementation, the programmer should always know that it is found in the source file (resp. template implementation file). The obvious exception to this rule is of course inline functions that must be defined in the header file. However, note that inline functions should be kept at a minimum.

37. File content must be kept within 80 columns.

80 columns is a common dimension for editors, terminal emulators, printers and debuggers, and files that are shared between several people should keep within these constraints. It improves readability when unintentional line breaks are avoided when passing a file between programmers.

38. Special characters like TAB and page break must be avoided.

These characters are bound to cause problem for editors, printers, terminal emulators or debuggers when used in a multi-programmer, multi-platform environment.

39. The incompleteness of split lines must be made obvious [1].

```
totalSum = a + b + c +  
           d + e;  
function (param1, param2,  
          param3);  
setText ("Long line split"  
         "into two parts.");  
for (int tableNo = 0; tableNo < nTables;  
     tableNo += tableStep) {  
    ...  
}
```

Split lines occurs when a statement exceed the 80 column limit given above. It is difficult to give rigid rules for how lines should be split, but the examples above should give a general hint.

In general:

- Break after a comma.
- Break after an operator.
- Align the new line with the beginning of the expression on the previous line.

## 4.2 Include Files and Include Statements

40. Header files must contain an include guard.

```
#ifndef COM_COMPANY_MODULE_CLASSNAME_H  
#define COM_COMPANY_MODULE_CLASSNAME_H  
:  
#endif
```

The construction is to avoid compilation errors. The name convention resembles the location of the file inside the source tree and prevents naming conflicts.

41. Include statements should be sorted and grouped. Sorted by their hierarchical position in the system with high level (local) files included first. Leave an empty line between groups of include statements.

```
#include "com/company/ui/MainWindow.h"  
#include "com/company/ui/PropertiesDialog.h"  
  
#include <qt/qtextfield.h>  
#include <qt/qbutton.h>  
  
#include <iomanip>  
#include <fstream>
```

In addition to show the reader the individual include files, it also give an immediate clue about the modules that are involved.

Include file paths must never be absolute. Compiler directives should instead be used to indicate root directories for includes.

The choice for this ordering comes from [6] :

“Latent usage errors can be avoided by ensuring that the .h file of a component parses by itself – without externally-provided declarations or definitions... Including the .h file as the very first line of the .cpp file ensures that no critical piece of information of information intrinsic to the physical interface of the component is missing from the .h file (or, if there is, that you will find out about as soon as you try to compile the .cpp file).”

If the order of header inclusion goes “from most specific to most general”, then it’s more likely that if your header doesn’t parse by itself, you’ll find out about it sooner and prevent annoyances down the road.

42. Include statements must be located at the top of a file only.

Common practice. Avoid unwanted compilation side effects by "hidden" include statements deep into a source file.

## 5 Statements

### 5.1 Types

43. Types that are local to one file only can be declared inside that file.

Enforces information hiding.

44. The parts of a class must be sorted public, protected and private [2][3]. All sections must be identified explicitly. Not applicable sections should be left out.

The ordering is "most public first" so people who only wish to use the class can stop reading when they reach the protected/private sections.

45. Type conversions must always be done explicitly. Never rely on implicit type conversion.

```
floatValue=static_cast<float>(intValue); //NOT: floatValue=intValue;
```

By this, the programmer indicates that he is aware of the different types involved and that the mix is intentional.

## 5.2 Variables

46. Variables should be initialized where they are declared.

This ensures that variables are valid at any time. Sometimes it is impossible to initialize a variable to a valid value where it is declared:

```
int x;  
int y;  
int z;  
getCenter(&x, &y, &z);
```

In these cases it should be left uninitialized rather than initialized to some phony value.

47. Variables must never have dual meaning.

Enhance readability by ensuring all concepts are represented uniquely. Reduce chance of error by side effects.

48. Use of global variables should be minimized.

In C++ there is no reason global variables need to be used at all. The same is true for global functions or file scope (static) variables.

49. Class variables should never be declared public.

The concept of C++ information hiding and encapsulation is violated by public variables. Use private variables and access functions instead. One exception to this rule is when the class is essentially a data structure, with no behavior (equivalent to a C struct). In this case it is appropriate to make the class' instance variables public [2].

Note that structs are kept in C++ for compatibility with C only, and avoiding them increases the readability of the code by reducing the number of constructs used. Use a class instead.



51. C++ pointers and references should have their reference symbol next to the type rather than to the name.

```
float* x; // NOT: float *x;  
int& y; // NOT: int &y;
```

The pointer-ness or reference-ness of a variable is a property of the type rather than the name. You can do this safely if you define one variable per line. C-programmers often use the alternative approach, while in C++ it has become more common to follow this recommendation.

53. Implicit test for 0 should not be used other than for boolean variables and pointers.

```
if (nLines != 0) // NOT: if (nLines)  
if (value != 0.0) // NOT: if (value)
```

It is not necessarily defined by the C++ standard that ints and floats 0 are implemented as binary 0. Also, by using explicit test the statement give immediate clue of the type being tested.

It is common also to suggest that pointers shouldn't test implicit for 0 either, i.e. `if (line == 0)` instead of `if (line)`. The latter is regarded so common in C/C++ however that it can be used.

54. Variables should be declared in the smallest scope possible.

Keeping the operations on a variable within a small scope, it is easier to control the effects and side effects of the variable.

## 5.3 Loops

55. Only loop control statements must be included in the `for()` construction.

```
sum = 0; // NOT: for (i = 0, sum = 0; i < 100; i++)  
for (i = 0; i < 100; i++) // sum += value[i];  
    sum += value[i];
```

Increase maintainability and readability. Make it crystal clear what controls the loop and what the loop contains.

56. Loop variables should be initialized immediately before the loop.

```
isDone = false;           // NOT: bool isDone = false;
while (!isDone) {         // :
    :                     // while (!isDone) {
}                          // :
                          // }
```

57. do-while loops can be avoided.

do-while loops are less readable than ordinary while loops and for loops since the conditional is at the bottom of the loop. The reader must scan the entire loop in order to understand the scope of the loop.

In addition, do-while loops are not needed. Any do-while loop can easily be rewritten into a while loop or a for loop. Reducing the number of constructs used enhance readability.

58. The use of break and continue in loops should be avoided.

These constructs can be compared to goto and they should only be used if they prove to have higher readability than their structured counterpart.

60. The form while(true) should be used for infinite loops.

```
while (true) {
    :
}

for (;;) { // NO!
    :
}

while (1) { // NO!
    :
}
```

Testing against 1 is neither necessary nor meaningful. The form for (;;) is not very readable, and it is not apparent that this actually is an infinite loop.

## 5.4 Conditionals

61. Complex conditional expressions must be avoided. Introduce temporary boolean variables instead [1].

```
bool isFinished = (elementNo < 0) || (elementNo > maxElement);
bool isRepeatedEntry = elementNo == lastElement;
if (isFinished || isRepeatedEntry) {
    :
}

// NOT:
if ((elementNo < 0) || (elementNo > maxElement) ||
    elementNo == lastElement) {
    :
}
```

By assigning boolean variables to expressions, the program gets automatic documentation. The construction will be easier to read and to debug.

62. The nominal case should be put in the if-part and the exception in the else-part of an if statement [1].

```
bool isOk = readFile (fileName);
if (isOk) {
    :
}
else {
    :
}
```

Makes sure that the exceptions don't obscure the normal path of execution. This is important for both the readability and performance.

63. The conditional should be put on a separate line.

```
if (isDone)                // NOT: if (isDone) doCleanup();
    doCleanup();
```

This is for debugging purposes. When writing on a single line, it is not apparent whether the test is really true or not.

64. Executable statements in conditionals must be avoided.

```
File* fileHandle = open(fileName, "w");
if (!fileHandle) {
    :
}

// NOT:
if (!(fileHandle = open(fileName, "w"))) {
    :
}
```

Conditionals with executable statements are just very difficult to read. This is especially true for programmers new to C/C++.

## 5.5 Miscellaneous

65. The use of magic numbers in the code should be avoided. Numbers other than 0 and 1 should be considered declared as named constants instead.

If the number does not have an obvious meaning by itself, the readability is enhanced by introducing a named constant instead. A different approach is to introduce a method from which the constant can be accessed.

66. Floating point constants should always be written with decimal point and at least one decimal.

```
double total = 0.0;    // NOT: double total = 0;
double speed = 3.0e8;  // NOT: double speed = 3e8;
double sum;
:
sum = (a + b) * 10.0;
```

This emphasize the different nature of integer and floating point numbers even if their values might happen to be the same in a specific case.

Also, as in the last example above, it emphasize the type of the assigned variable (sum) at a point in the code where this might not be evident.

67. Floating point constants should always be written with a digit before the decimal point.

```
double total = 0.5; // NOT: double total = .5;
```

The number and expression system in C++ is borrowed from mathematics and one should adhere to mathematical conventions for syntax wherever possible. Also, 0.5 is a lot more readable than .5; There is no way it can be mixed with the integer 5.

68. Functions must always have the return value explicitly listed.

```
int getValue() // NOT: getValue() { : }
```

If not explicitly listed, C++ implies `int` return value for functions. A programmer must never rely on this feature, since this might be confusing for programmers not aware of this artifact.

69. `goto` should not be used.

`Goto` statements violates the idea of structured code. Only in some very few cases (for instance breaking out of deeply nested structures) should `goto` be considered, and only if the alternative structured counterpart is proven to be less readable.

70. "0" should be used instead of "NULL".

NULL is part of the standard C library, but is made obsolete in C++.

## 6 Layout and Comments

### 6.1 Layout

71. Basic indentation should be 2.

```
for (i = 0; i < nElements; i++)  
    a[i] = 0;
```

Indentation of 1 is too small to emphasize the logical layout of the code. Indentation larger than 4 makes deeply nested code difficult to read and increase the chance that the lines must be split. Choosing between indentation of 2, 3 and 4, 2 and 4 are the more common, and 2 chosen to reduce the chance of splitting code lines.

72. Block layout should be as illustrated in example 1 below (recommended) or example 2, and must not be as shown in example 3 [4]. Function and class blocks must use the same block layout.

```
while (!done) {  
    doSomething();  
    done = moreToDo();  
}
```

```
while (!done)  
{  
    doSomething();  
    done = moreToDo();  
}
```

```
while (!done)  
{  
    doSomething();  
    done=moreToDo();  
}
```

Example 3 introduces an extra indentation level which doesn't emphasize the logical structure of the code as clearly as example 1 and 2.

73. The class declarations should have the following form:

```
class SomeClass : public BaseClass {  
public:  
    ...  
protected:  
    ...  
private:  
    ...  
}
```

This follows partly from the general block rule above.

74. Method definitions should have the following form:

```
void someMethod() {  
    ...  
}
```

This follows from the general block rule above.

75. The if-else class of statements should have the following form:

```
if (condition) {  
    statements;  
}  
  
if (condition) {  
    statements;  
}  
else {  
    statements;  
}  
  
if (condition) {  
    statements;  
}  
else if (condition) {  
    statements;  
}  
else {  
    statements;  
}
```

This follows partly from the general block rule above. However, it might be discussed if an else clause should be on the same line as the closing bracket of the previous if or else clause:

```
if (condition) {  
    statements;  
} else {  
    statements;  
}
```

The chosen approach is considered better in the way that each part of the if-else statement is written on separate lines of the file. This should make it easier to manipulate the statement, for instance when moving else clauses around.

76. A for statement should have the following form:

```
for (initialization; condition; update) {  
    statements;  
}
```

This follows from the general block rule above.



77. An empty for statement should have the following form:

```
for (initialization; condition; update)
    ;
```

This emphasize the fact that the for statement is empty and it makes it obvious for the reader that this is intentional. Empty loops should be avoided however.

78. A while statement should have the following form:

```
while (condition) {
    statements;
}
```

This follows from the general block rule above.

79. A do-while statement should have the following form:

```
do {
    statements;
} while (condition);
```

This follows from the general block rule above.

80. A switch statement should have the following form:

```
switch (condition) {  
    case ABC :  
        statements;  
        // Fallthrough  
  
    case DEF :  
        statements;  
        break;  
  
    case XYZ :  
        statements;  
        break;  
  
    default :  
        statements;  
        break;  
}
```

Note that each case keyword is indented relative to the switch statement as a whole. This makes the entire switch statement stand out. Note also the extra space before the : character. The explicit Fallthrough comment should be included whenever there is a case statement without a break statement. Leaving the break out is a common error, and it must be made clear that it is intentional when it is not there.

81. A try-catch statement should have the following form:

```
try {  
    statements;  
}  
catch (Exception& exception) {  
    statements;  
}
```

This follows partly from the general block rule above. The discussion about closing brackets for if-else statements apply to the try-catch statements.

82. Single statement if-else, for or while statements can be written without brackets.

```
if (condition)
    statement;

while (condition)
    statement;

for (initialization; condition; update)
    statement;
```

It is a common recommendation that brackets should always be used in all these cases. However, brackets are in general a language construct that groups several statements. Brackets are per definition superfluous on a single statement. On the other hand, it should be noted that brackets must be used when dealing with possibly ambiguous nested if-else statements.

83. The function return type can be put in the left column immediately above the function name.

```
void
MyClass::myMethod(void) {
    :
}
```

This makes it easier to spot function names within a file since they all start in the first column.

## 6.2 White Space

84.

- Conventional operators should be surrounded by a space character.
- C++ reserved words should be followed by a white space.
- Commas should be followed by a white space.
- Colons should be surrounded by white space.
- Semicolons in for statements should be followed by a space character.

```
a = (b + c) * d; // NOT: a=(b+c)*d
```

```
while (true) // NOT: while(true)
{
```

```
    ...
```

```
doSomething(a, b, c, d); // NOT: doSomething(a,b,c,d);
```

```
case 100 : // NOT: case 100:
```

```
for (i = 0; i < 10; i++) { // NOT: for(i=0;i<10;i++)
{
```

Makes the individual components of the statements stand out. Enhances readability. It is difficult to give a complete list of the suggested use of whitespace in C++ code. The examples above however should give a general idea of the intentions.

85. Method names can be followed by a white space when it is followed by another name.

```
doSomething (currentFile);
```

Makes the individual names stand out. Enhances readability. When no name follows, the space can be omitted (`doSomething()`) since there is no doubt about the name in this case.

An alternative to this approach is to require a space after the opening parenthesis. Those that adhere to this standard usually also leave a space before the closing parentheses: `doSomething ( currentFile );`. This does make the individual names stand out as is the intention, but the space before the closing parenthesis is rather artificial, and without this space the statement looks rather asymmetrical (`doSomething( currentFile);`).

86. Logical units within a block should be separated by one blank line.

```
Matrix4x4 matrix = new Matrix4x4();  
  
double cosAngle = Math.cos(angle);  
double sinAngle = Math.sin(angle);  
  
matrix.setElement(1, 1, cosAngle);  
matrix.setElement(1, 2, sinAngle);  
matrix.setElement(2, 1, -sinAngle);  
matrix.setElement(2, 2, cosAngle);  
  
multiply(matrix);
```

Enhance readability by introducing white space between logical units of a block.

87. Methods should be separated by three blank lines.

By making the space larger than space within a method, the methods will stand out within the file.

88. Variables in declarations can be left aligned.

```
AsciiFile* file;  
int        nPoints;  
float      x;
```

Enhance readability. The variables are easier to spot from the types by alignment.

89. Use alignment wherever it enhances readability.

```
if      (a == lowValue)    computeSomething();
else if (a == mediumValue) computeSomethingElse();
else if (a == highValue)   computeSomethingElseYet();

value = (potential        * oilDensity) / constant1 +
        (depth            * waterDensity) / constant2 +
        (zCoordinateValue * gasDensity) / constant3;

minPosition    = computeDistance(min,    x, y, z);
averagePosition = computeDistance(average, x, y, z);

switch (value) {
  case PHASE_OIL :   strcpy(phase, "Oil");   break;
  case PHASE_WATER : strcpy(phase, "Water"); break;
  case PHASE_GAS :   strcpy(phase, "Gas");   break;
}
```

There are a number of places in the code where white space can be included to enhance readability even if this violates common guidelines. Many of these cases have to do with code alignment. General guidelines on code alignment are difficult to give, but the examples above should give a general clue.

## 6.3 Comments

90. Tricky code should not be commented but rewritten! [1]

In general, the use of comments should be minimized by making the code self-documenting by appropriate name choices and an explicit logical structure.

91. All comments should be written in english [2].

In an international environment english is the preferred language.

92. Use // for all comments, including multi-line comments.

```
// Comment spanning  
// more than one line.
```

Since multilevel C-commenting is not supported, using // comments ensure that it is always possible to comment out entire sections of a file using /\* \*/ for debugging purposes etc.

There should be a space between the "/" and the actual comment, and comments should always start with an upper case letter and end with a period.

93. Comments should be indented relative to their position in the code. [1]

```
while (true) {           // NOT: while (true) {  
    // Do something      //      // Do something  
    something();         //      something();  
}                         //      }
```

This is to avoid that the comments break the logical structure of the program.

94. Class and method header comments should follow the JavaDoc/Doxygen conventions.

```
/** @class Object  
 *  @brief Base class for most sofa classes  
 *  
 *  Object is the highest base class for most sofa objects.  
 *  It provides basic debug flags/methods.  
 */
```

Regarding standardized class and method documentation the Java development community is much more mature than the C/C++ one. This is due to the standard automatic Javadoc tool that is part of the development kit and that help producing high quality hypertext documentation from these comments.

There are Javadoc-like tools available also for C++. These follows the same tagging syntax as Javadoc. See for instance [Doc++](#) or [Doxygen](#).

## 8 References

- [1] Code Complete, Steve McConnell - Microsoft Press
- [2] Programming in C++, Rules and Recommendations, M Henricson, e. Nyquist, Ellemtel (Swedish telecom)  
<http://www.doc.ic.ac.uk/lab/cplus/c%2b%2b.rules/>
- [3] Wildfire C++ Programming Style, Keith Gabryelski, Wildfire Communications Inc.  
<http://www.wildfire.com/~ag/Engineering/Development/C++Style/>
- [4] C++ Coding Standard, Todd Hoff  
<http://www.possibility.com/Cpp/CppCodingStandard.htm>
- [5] Doxygen documentation system  
<http://www.stack.nl/~dimitri/doxygen/index.html>
- [6] Large-Scale C++ Software Design, John Lakos – Addison-Wesley

---

© 2006 Geotechnical Software Services. All rights reserved.

This page is maintained by [webmaster@geosoft.no](mailto:webmaster@geosoft.no)

